

P/8248/US/CA

- 8 -

CLAIMS

1. A continuous wave ranging system, comprising an, r.f. generator for generating an r.f. carrier wave/a modulator for modulating said r.f. carrier waxe in accordance with a pseudo random code, a transmitting antenna for radiating a modulated signal from said modulator towards a target, a receiving antenna and receiver for detecting a signal reflexted back from said target, a correlator for correlating said reflected back from the target with said pseudo random a/ selected code which incorporates phase shift corresponding to a current range gate to be tested, whereby the range of the target from the system may be determined, a store containing a plurality of different pseudo random codes, and selector means arranged to supply to the modulator and to the correlator a code from said store whose sidelobe characteristics are suitable for a next range gate to be tested.

2. A system as claimed in claim 1, wherein a plurality of codes are selected from the store and used in a sequence which substantially eliminates the effect of breakthrough sidelobes.



P/8248/US/CA

- 9 -

A system as claimed in claim 2, wherein said plurality of codes are selected on a basis of suitability for use in future envisaged ranges.

A. A system as claimed in claim 3, wherein range is scanned increasingly, codes suitable for the longest ranges being selected.

5. A system as claimed in claim 3, wherein said plurality of codes is selected to reduce the number of code changes required when scanning different ranges.

CONFODENTIAL DECLASSIFIED BY CHATTAGENCY